®Glutoclean

Stain remover

Technical Data Sheet

400ml / Item number 015101092 / EAN 4044899151913



Simply by spraying it on, it quickly and permanently removes stains and water-soluble dirt, such as water stains, soot, grime, grease, fuel oil, nicotine, pencil marks and the like. It prevents stains from showing through after wallpapering or painting the surface with emulsion paints.

Not suitable for solvent-based markers. The product can be used both indoors and outdoors.

Do not use the stain-blocking product on surfaces that may be damaged by solvents, e.g. polystyrene.

- on walls and ceilings
- white
- quick-drying
- for outdoor and indoor use

Area of application

For quick and easy covering of all stains on walls and ceilings. White in colour. Quick-drying. Suitable for both exterior and interior use.

Preparation

The substrate must be solid, dry, dust-free and resistant to solvents.

Processing

Shake the container well before use. Then carry out a test spray. From a distance of 20 cm, spray the soiled area so that it is completely covered. Repeat the treatment on rough surfaces or in cases of very heavy soiling. After 10 minutes, you can begin wallpapering or painting on the treated surface.

After use, clean the spray nozzle by pressing it whilst holding the container upside down.

Storage

Store in a cool, dry place! This product is frost-resistant.
Keep away from sources of ignition!
Shelf life: at least 48 months from the date of manufacture

Notes

Flammable aerosols. Pressurised container: may explode if heated. Harmful to aquatic life with long-lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Keep out of the reach of children. Use only outdoors or in a well-ventilated area. Do not direct the spray onto an open flame or other sources of ignition. Avoid inhaling vapours or spray mist. Wear protective gloves and eye protection. IF INHALED: Move the affected person to fresh air and ensure they remain completely at rest in a position that facilitates breathing. IF IN THE EYES: Gently rinse eyes with water for several minutes. Remove contact lenses, if worn and if this can be done easily. Continue rinsing the eyes. Dispose of the contents/container in accordance with local disposal regulations. Pressurised container: Do not pierce or burn, even after use.
Keep away from sunlight and do not expose to temperatures exceeding 50°C / 122°F. Keep away from heat, sparks, open flames and hot surfaces.

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.

Do not smoke in the vicinity.

Contains: Hydrocarbons, C6–C7, n-alkanes, isoalkanes, cycloalkanes, < 5 % n-hexane, Hydrocarbons, C9–C10, n-alkanes, isoalkanes, cycloalkanes, < 2 % aromatic compounds.

Base ingredients: alkyd resin, titanium dioxide, solvent
Gas generator: propane and butane gas, free from ODS

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.