®Glutoclean

Rohr Frei Gel

Technical Data Sheet

1l / Item number 037703074 / EAN 4044899377030
1l / Item number 037703092 / EAN 4044899377931



A powerful drain cleaner for dissolving and breaking down stubborn blockages and eliminating unpleasant odours. Suitable for all metal and plastic drain and pipework systems in the kitchen and bathroom – e.g. washbasins, sinks, shower trays and toilets.

- for the kitchen, bathroom and toilet
- highly effective
- unblocks the drain
- automatic operation without the generation of heat

Area of application

Drain cleaner for the kitchen, bathroom and home: clears blockages, grease, hair and soap scum, eliminates odours and reliably protects your pipes.

Processing

If the drain is blocked, remove the accumulated water and pour 200 ml of Rohr Frei Gel into the drain opening. After leaving it to work for approx. 30 minutes, rinse thoroughly with warm water. For very stubborn blockages, repeat the cleaning process using a higher dose if necessary and extend the application time (overnight). To prevent odours, pour 50 ml of Rohr Frei Gel down the drain once a week and leave it to work overnight.

Storage

Keep the container tightly closed and store in a cool place, away from frost. Keep out of the reach of children.

Notes

Wash off any splashes on delicate surfaces, such as wood, varnish, certain plastics, wallpaper, carpets, textiles and aluminium, immediately with water.

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.