®Glutoclean

Mould-blocking paint

Technical Data Sheet

750ml / Item number 013401092 / EAN 4044899134916



A white, specialised, mould-inhibiting paint for surfaces prone to mould growth. It can also be applied to substrates with residual moisture. Once dry, it prevents moisture from escaping from the treated surface, thereby protecting the painted surface from the formation of new mould without the use of biocidal additives.

- effectively prevents the appearance of damp and mould
- also for substrates with residual moisture
- white

Area of application

It is used to protect walls and ceilings prone to mould growth in residential premises and in rooms with high humidity.

Processing

Before applying Glutoclean Mould-Blocking Paint, any existing mould on the surface to be treated must first be removed using the Glutoclean range of mould-removal products.
Carefully remove any loose or flaking areas of plaster and level them with Glutoclean Mould-Resistant Filler.
The surface must be sound and free from contaminants (dust, dirt, grease). Stir Glutoclean Mould-Blocking Paint thoroughly before use and apply to the surface with a brush or a solvent-resistant roller. The surface must be painted evenly without any gaps. For reliable protection, we recommend painting approximately 20 per cent beyond the edges of the affected surface.
If necessary, apply a second coat once the first has dried completely.
Drying time depends on the temperature and humidity of the air, as well as on the moisture content of the surface being painted.

Storage

Shelf life: at least 48 months from the date of manufacture.
Store in a cool place and keep tightly sealed.

Notes

All subsequent work (painting, wallpapering), as well as the application of other anti-mould products from the Glutoclean range, should only be carried out once the paint has dried completely. Wash tools immediately after use with a solvent-based cleaner. Not recommended for application to damp plaster surfaces. If the substrate has been exposed to prolonged moisture, consult a specialist.
Keep out of the reach of children.
Use only in well-ventilated areas. If swallowed, do not induce vomiting; seek medical advice immediately and show the packaging and label to the doctor. Store containers in a well-ventilated area. Do not smoke. Do not inhale vapours. Avoid contact with eyes and skin. In case of contact with eyes, rinse thoroughly with water and seek medical advice.

Base ingredients: acrylic resin, titanium dioxide, cement, solvent, additives
Density: approx. 1.40 g/cm³
Colour: matt white
Flash point: 65°C
Coverage: approx. 300 ml/m²

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.