®Glutoclean

Anti-mould primer

Technical Data Sheet

1l / Item number 047303092 / EAN 4044899473930



Extra protection for surfaces prone to mould growth. Glutoclean Mould-Resistant Primer is weather- and moisture-resistant and dries to a clear finish.

- additional protection against mould growth
- for indoor and outdoor use
- 1 litre per 10 m²

Area of application

A hydrozole-acrylate, deep-penetrating primer designed to provide additional protection against mould and to strengthen porous, sandy and chalky substrates, both indoors and outdoors.

Processing

The surface must be free from any substances that may prevent adhesion (oil, grease).
Remove any loose plaster or masonry. Remove any mould present on the surface using PUFAS Mould Remover.
Glutoclean Anti-Mould Primer is ready for use and can be applied to the surface with a paintbrush, brush, roller or suitable sprayer.
It is recommended to prime highly absorbent substrates twice.

Avoid splashing the product onto surfaces not intended for treatment.
Rinse used tools with water immediately after application.

Consumption

1 litre per 10 m²

Storage

This product is frost-resistant!
If it freezes, allow it to thaw at room temperature.
Shake the container well before use.
Store in a cool place and keep tightly closed!
Shelf life: at least 60 months from the date of manufacture

Notes

Keep out of the reach of children.

Base: hydrozol-acrylate dispersion
pH: 7
Density: approx. 1.0 g/cm³
Coverage: 250 ml/m² depending on the surface

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.