®Glutoclean

# FRP Facade Cleaner

Technical Data Sheet

5l / Item number 031805074 / EAN 4044899318057




Specialist cleaner for façades, roofs, patios, garages, fences, pavements and similar surfaces. For mineral surfaces (such as concrete, render, stone, brick, patio slabs, tiles and ceramics) as well as for glass, roofing felt and similar outdoor surfaces. Automatically removes organic dirt. Prevents re-soiling.

- self-cleaning
- penetrating
- odourless
- ideal for sprayers
- ready to use

## Area of application

Automatically removes organic dirt. Prevents dirt from re-accumulating.

## Processing

Die zu behandelnde Fläche muss trocken und wärmer als +5 °C sein. Den Fassadenreiniger mit einem geeigneten Niederdruck-Sprühgerät, einer Gartenspritze oder einer Bürste satt auftragen und mindestens 36 Stunden einwirken lassen. In der Regel ist keine weitere Bearbeitung der behandelten Fläche notwendig. Nur bei sehr starken Verunreinigungen kann es erforderlich sein, die Rückstände mit einer Bürste zu entfernen oder den Auftrag zu wiederholen. Die behandelte Fläche muss nur bei Bedarf mit Wasser nachgewaschen werden; das Schmutzwasser ist gesetzeskonform aufzufangen. Arbeitsgeräte nach Gebrauch reinigen. Nicht in die Kanalisation oder Gewässer gelangen lassen.

## Consumption

1 l reicht für ca. 10 m²

## Storage

Gebinde gut verschlossen und kühl, aber frostfrei lagern.
Für Kinder unzugänglich aufbewahren.



Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

**Note:**
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.