®Glutoclean

Brick & Paving Oil

Technical Data Sheet

1l / Item number 030903205 / EAN 4250295100909



Deepens and refreshes colours without leaving a sheen, thereby emphasising the material’s natural appearance and surface texture. Reduces the penetration of stains and dirt. Porous surfaces become more dirt- and water-repellent and are therefore easier to maintain. For initial and follow-up treatment of absorbent substrates such as clinker, paving, brick, slate, cotto, clay slabs, unglazed ceramic tiles, split-face and dry-pressed tiles. Suitable for indoor and outdoor use.

- for clinker, bricks, clay, split and dry-pressed slabs
- enhances and refreshes colour
- protects against dirt and stains
- for indoor and outdoor use
- 1 litre is sufficient for approx. 15–20 m²

Area of application

Colour enhancer revitalises natural stone and matt porous surfaces, protecting them from stains, dirt and water – for indoor and outdoor use.

Processing

Before application, the surface must be dry, clean and free from stains. Apply ‘Klinker und Pflaster-Öl’ thinly and evenly using a short-pile synthetic fibre roller or a soft brush. Apply only as much as the surface can absorb (avoid puddling). Blot up any excess with an absorbent cloth. For highly absorbent or porous materials, it is advisable to apply several coats at 15-minute intervals. Protect the treated surfaces from moisture for at least
24 hours.

Storage

Keep the container tightly closed and store in a cool place, away from frost. Keep out of the reach of children.

Notes

Not suitable for non-absorbent floor coverings. Surfaces must be thoroughly dry. Allow the surface to dry for at least 48 hours after deep cleaning. If necessary, test on an inconspicuous area before use. Substrate temperature during application: +5 °C to +25 °C. Switch off underfloor heating at least 12 hours before application.

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user’s responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.