®Glutoclean

Porcelain stoneware impregnation

Technical Data Sheet

1l / Item number 035303074 / EAN 4044899353034



Permanently impregnates surfaces and provides invisible protection against dirt and signs of wear. The treated surface is easy to clean and protected against re-soiling, e.g. by oil, grease and water stains. Suitable for all surfaces made of polished, matt, honed and textured porcelain stoneware or stoneware, both indoors and outdoors. For treating tables, walls, floors or worktops. Also suitable for porous surfaces such as cement grout lines.

- provides long-lasting protection against dirt and signs of wear and tear
- for polished, matt, honed and textured porcelain stoneware
- can also be used as a joint sealant
- for indoor and outdoor use

Area of application

Protective impregnation for kitchens, bathrooms, hallways and living areas: provides invisible protection for surfaces against dirt, oil, grease and water stains indoors.

Processing

Use only on dry surfaces. The surface must be cleaned beforehand. Apply the impregnating agent undiluted using a paint roller or brush, in a thin but even coat. Effectiveness can be enhanced by a further wet-on-wet application. When doing so, do not apply more impregnating agent than the surface can absorb. After application, leave to
set for 50 minutes. Wipe up any excess liquid with an absorbent, dry cloth. No streaks must remain. Dried residues can be removed with a cloth that has been soaked in the impregnating agent beforehand. The subsequent drying time for the impregnating agent is 3–4 hours. The surface must not be walked on or treated with moisture during this drying phase. The product takes full effect after 24 hours.

Storage

Keep the container tightly closed and store in a cool place, away from frost. Keep out of the reach of children.

Notes

When treating larger areas, always work in small sections. Protect and cover solvent-sensitive surfaces or glass before application. When using as a joint protector, apply only to clean, stain-free, dry and fully cured joints to ensure the impregnation takes effect evenly and no colour changes occur.

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user's responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.