®Glutoclean

Stone Sealing

Technical Data Sheet

1l / Item number 035403074 / EAN 4044899354031



Sealant providing long-lasting protection for stone (suitable for all absorbent natural and artificial stone surfaces, precast concrete blocks, exposed aggregate concrete, slate, marble, sandstone, terrazzo, porphyry, Solnhofen tiles, concrete surfaces and similar) for both indoor and outdoor use. For treating floors, stairs and window sills, as well as patios and balconies. The waterproof, UV-resistant protective coating with a satin sheen makes the treated surface dirt-repellent and easy to maintain. The appearance, colour and texture of the stone are enhanced and preserved in the long term. The protective coating is non-yellowing and hard-wearing.

- provides long-lasting protection against dirt and signs of wear and tear
- for polished, matt, honed and textured porcelain stoneware
- can also be used as a joint sealant
- for indoor and outdoor use

Area of application

Stone sealant for patios, balconies, gardens and façades: protects against dirt, UV rays and moisture, and permanently enhances colour, texture and a silky sheen.

Processing

Use only on dry surfaces. The surface must be cleaned beforehand. Apply the sealant undiluted in a thin, even layer using a paint roller or brush. Do not apply more than the surface can absorb. Do not apply too much; avoid the formation of puddles. No streaks must be left behind. For larger areas, always work in sections
. The subsequent drying time is approx. 2 hours. The area must not be walked on during this drying phase. Subsequently, protect the sealed area from moisture for 2 days.

Storage

Store the container tightly sealed in a cool place, but away from frost. Keep out of the reach of children.

Notes

Floor surfaces must be protected against moisture rising from the substrate. Any white patches that appear after drying indicate moisture in the stone. Cover glass and solvent-sensitive surfaces during application. Do not apply at temperatures below +12 °C. Non-absorbent, polished or finely ground surfaces cannot be sealed.

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden Tel.: +49(0)55 41 / 70 03-03 · www.glutoclean.de · info@glutolin.de

Note:
All information and data contained in this information sheet are based on our practical experience and laboratory tests, and reflect the current state of the art. However, they can only serve as general guidance and do not constitute a guarantee of properties. As the conditions under which storage, transport and processing take place are beyond our control, no legal obligation can be derived from this guidance. It is the user’s responsibility to test the products for their suitability for the intended purpose under the relevant site conditions.