

# ® **Glutoclean**

## Clinker and Pavement Oil

### Description

For clinkers, paving, slate, bricks as well as clay, split and dry hardboards. Colour-enhancing and shine-restoring. Protects against dirt and stains. For inside and out.

### Effect

Acts colour-enhancing and shine-restoring without shining thus emphasising material naturalness and surface structure. Reduces penetration of stains and dirt. Porous surfaces become more dirt and water-repelling and, hence, easier to clean.

### Area of application

For initial and post-treatment of absorbent clinker, paving, brick, slate, cotto, clay slabs, unglazed ceramic slabs, split and dry hardboard sub-floors. Can be used both indoors and outdoors.

### Application

The coating must be dry, clean and free from stains prior to usage. Apply Glutoclean Clinker and Pavement Oil using a plastic roller or soft brush thinly and evenly. Apply only the quantity that the sub-floor can absorb (avoid formation of puddles). Collect any excess using an absorbent cloth. In case of strongly absorbent or porous materials, repeated coating at 15 minute intervals is recommended. The treated surfaces should be protected against effects of moisture at least for 24 hours.

### Note

Unsuitable for non-absorbent floorings. The areas must be well dried. Let areas dry at least 48 hours after initial cleaning. Test at an inconspicuous area before if need be. Sub-floor temperature should range from +5 °C up to +25 °C for processing. Switch off any under-floor heating at least 12 hours before processing.

### Technical data

- Density: 0.85 g/ml
- pH value: n/a
- Appearance: transparent
- Odour: neutral

### Safety notes

- Keep out of the reach of children.



### Packaging unit

1000 ml bottle (4 items in carton)

### Order No. 390 309

Info telephone: +49(0) 55 41 / 70 03 - 491

The conditions of use and fields of application of our products are very varied. We can provide only general processing directives in the product information. We can and should advise you in a non-binding way only. The utilisation of the products is to be checked and adapted to local factors and the surfaces to be treated. In all cases of doubt, or if there is no experience available, the product is always to be tried out beforehand at an inconspicuous location. We would be glad to advise you in case of special requirements.

We are liable for incomplete or false specifications in our informative data sheet only in case of major culpability (intent or gross negligence).