

Algae and Mould Remover

Properties:

- ready-to-use
- highly effective on stone, render, ceramics, concrete etc.
- for patios, pathways, garages, fences, roofs, facades etc.
- deep-penetrating, self-cleaning
- · chlorine-free and odourless
- · ideal for spray equipment

Action:

Reliably removes algae, mould and similar green growth.

Areas of application:

For terraces, pathways, garages, fences, roofs, facades and the like.

Application:

Apply Algae and Mould Remover with pressure spray equipment or brush and allow to work for at least 24 hours. A single application normally suffices. In case of very heavy soiling, it may be necessary to brush off residue or repeat treatment. Treated surfaces should be washed down prior to application of subsequent coatings or impregnations. Wash tools with water after use.

Consumption:

5 ltr suffice for approx. 50 m².

Technical data:

Constituents: Quaternary ammonium salt, non-ionic

surfactant, water and additives

Density: Approx. 1 g/cm³

pH value: 7 – 8 Appearance: Liquid

Odour: Characteristic

Storage:

Store in cool, though frost-free environment in properly sealed containers.

Store separately from foodstuffs and keep out of reach of children.

Please consult safety data sheet for safety-relevant data. Up-to-date safety data sheets are available from our website at www.glutoclean.de or from sde@glutolin.de.

Medical emergency number: +49 (0) 551 / 19240

 Item No.
 EAN
 Container size

 007005057
 4044899070054
 5 ltr



Status: 24.04.2023

Glutolin Renovierungsprodukte GmbH Im Schedetal 1 · 34346 Hann. Münden

Tel.: +49(0)55 41 / 70 03-03 \cdot www.glutoclean.de \cdot info@glutolin.de

Note